



HighLight Plus

HIGH-END STROBOSCOPE

DESCRIPTION

HighLight Plus is a continuous and stroboscopic light source based on LED technology.

LIGHT SOURCE

Technology: White LED
 Color temperature: 6800° K
 Light intensity: 2,000 lumens
 Light lifetime: 20,000 hours

MAIN UNIT

Light cable connector: standard Storz. Olympus and Wolf available upon request
 Display: Monochrome graphic LCD 128x64pixels
 Information on the display: F0, motion speed, voice intensity and power spectrum
 Microphones: two interchangeable microphones supplied with the device, one contact microphone and one clip-on microphone
 Controls: through buttons, knob and the included dual footswitch

OPERATION

Operating modes: stroboscopic light / continuous light
 F0 range: 70 – 1,100 Hz
 Stroboscopic modes: Slow motion, Freeze
 Slow motion speed: 0.5 Hz, 1 Hz, 1.5 Hz
 Blinking frequency: automatically determined (based on the current F0) or manually selected

OUTPUTS

Audio: patient's voice on a mono 3.5 mm jack
 USB: sends to the PC the current F0, intensity and motion speed – Requires Daisy-Visia software to be displayed

POWER SUPPLY

Power supply: 100-240 Vac 50/60 Hz
 Replaceable fuses: 2 x T 2.5A, 5 x 20 mm delayed 250V anti-surge

MECHANICS

Size (WxHx): 30 x 11 x 29 cm / 11.81 x 4.33 x 11.42 in
 Weight: 5.0 kg / 11.02 lbs

FREIGHT PACKING

Size (WxDxH): 37.7 x 29 x 37.7 cm / 14.84 x 11.42 x 14.84 in
 Gross weight: 7.0 Kg / 15.43 lbs

APPLICABLE STANDARDS

IP classification: IPX0
 Electrical safety: IEC 60601-1
 EMC: IEC 60601-1-2

MDR CLASSIFICATION

MDR (EU) 2017/745 classification: Class I without a measuring function
 Classification rule (Annex VIII, MDR (EU) 2017/745): 10

PRODUCT CODES

10353: HighLight model Plus - LED stroboscope

INCLUDED PARTS

- Control Unit
- Dual footswitch
- Clip-on microphone
- Contact microphone
- USB A-B cable
- Stereo 3.5mm audio cable
- User manual

OPTIONAL PARTS (with order code)

- 10376: Olympus light cable adapter
- 10440: Wolf light cable adapter
- 10408: Light cable, 4.8 x 1800 mm, autoclavable
- 10524: Light cable, 4.8 x 2300 mm, autoclavable